














	CeDUR	wood shake	other synthetic shake	stone coated steel panels	concrete & clay tile
 <b>Class A Fire Rating without the requirement of special fire resistant underlayment</b>	Yes	No	No	Yes	Yes
 <b>Molded from natural cedar shakes</b>	Yes Available in 3 natural wood colors and molded from natural cedar shakes	Yes	No	No	No
 <b>Class 4 Impact Resistant UL2218</b>	Yes	No	Yes	Yes	Cracks easily, hail can cause severe damage
 <b>Certified to 115 mph wind gusts</b>	Yes	No	No	Yes	Wind damage not covered
 <b>Freeze/Thaw Resistant</b>	Yes	No	Yes although ice may accumulate in the cavity back	Yes	No not waterproof, can absorb 15% of water weight when wet
 <b>Solid product with color throughout (no cavity back)</b>	Yes	Yes	No cavity back creates need for special flashing and allows insects/debris buildup	No	Yes
 <b>Required Maintenance</b>	Low	High fire resistance maintenance required	Moderate replacement for breakage/curling	Low	Moderate to High -broken tiles
 <b>Multiple Widths including 12"</b>	Yes	Yes-but limited	Limited	No	No
 <b>Life Cycle Costs</b>	Low Life Cycle Costs	High costs	Medium costs cleaning debris from behind	Low life cycle costs	High costs due to breakage Lifespan is 20-50 years
 <b>3/4" Standard Thickness</b>	Yes	Yes available but not standard	No	No	No
 <b>Weight</b>	1.70 lbs/sq ft	1.5-2 lbs/sq ft	2.5-3 lbs/sq ft	1.25-1.75 lbs/sq ft	6-15 lbs/sq ft
 <b>Improves Insulation of Roof</b>	Yes	Wood shake would have some r value	No	No	No
 <b>Warranty</b>	50 Year Limited Material Warranty	limited warranty	50 year limited material warranty	lifetime limited material warranty	25-50 year warranty